

■ 6段ESPブーム性能表

カウンタウエイト 94t、アウトリガ張出幅 9.0m、アシストジャッキ

6段ESPブーム

単位:t

ブーム長さ(m) 作業半径(m)	15.0	19.5	24.0	28.5	33.0	37.6	42.1	46.6	51.1	55.6	60.1	64.0	m
3.0	170.0	170.0											3.0
3.5	170.0	170.0	170.0										3.5
4.0	170.0	170.0	170.0										4.0
4.5	170.0	170.0	170.0	170.0									4.5
5.0	170.0	170.0	170.0	170.0									5.0
6.0	170.0	170.0	170.0	170.0	170.0								6.0
7.0	170.0	170.0	170.0	170.0	170.0	170.0							7.0
8.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0						8.0
9.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	147.0	119.6				9.0
10.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	147.0	119.6	94.2			10.0
11.0	145.8	149.4	150.5	153.2	151.9	149.7	147.9	145.2	119.6	94.2	76.4		11.0
12.0	126.0	129.3	132.7	132.9	131.7	130.5	129.3	127.6	119.6	94.2	76.4	66.8	12.0
14.0		100.8	104.0	104.1	103.0	101.9	100.7	101.0	99.9	94.2	76.4	66.8	14.0
16.0		82.9	84.6	84.7	83.6	82.6	81.4	82.5	83.5	81.7	73.7	66.8	16.0
18.0			70.8	70.8	69.7	68.7	67.6	68.6	69.5	69.3	69.4	64.3	18.0
20.0			60.4	60.3	59.3	58.2	59.0	61.4	60.7	59.7	59.0	59.0	20.0
22.0			52.6	52.2	51.1	51.6	53.7	53.1	52.5	51.4	50.7	50.7	22.0
24.0				45.8	44.6	47.5	47.1	46.5	45.8	44.8	44.1	44.1	24.0
26.0				40.7	40.2	42.1	41.7	41.1	40.4	39.4	38.6	38.6	26.0
28.0					37.6	37.6	37.2	36.6	35.9	34.9	34.1	34.1	28.0
30.0					34.2	33.9	33.4	32.8	32.0	31.1	30.3	30.3	30.0
32.0						30.7	30.2	29.5	28.8	27.8	27.0	27.0	32.0
34.0						28.1	27.4	26.7	25.9	24.9	24.1	24.1	34.0
36.0							25.0	24.3	23.5	22.5	21.6	21.6	36.0
38.0							23.0	22.2	21.3	20.3	19.4	19.4	38.0
40.0							21.5	20.3	19.4	18.4	17.5	17.5	40.0
42.0								18.8	17.8	16.7	15.8	15.7	42.0
44.0								17.5	16.3	15.2	14.2	14.2	44.0
46.0									15.0	13.8	12.8	12.8	46.0
48.0									13.9	12.6	11.5	11.5	48.0
50.0										11.5	10.4	10.3	50.0
52.0										10.6	9.3	9.3	52.0
54.0											8.3	8.2	54.0
56.0											7.5	7.3	56.0
58.0											6.8	6.5	58.0
60.0												5.7	60.0
62.0												5.2	62.0
標準フック	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	150t	150t	

カウンタウエイト 0t、アウトリガ張出幅 2.6m

6段ESPブーム

単位:t

ブーム長さ(m) 作業半径(m)	15.0	19.5	24.0	※15.0	※19.5	※24.0	m
3.0	15.0			15.0			3.0
3.5	15.0	15.0		15.0	15.0		3.5
4.0	15.0	15.0	15.0	15.0	15.0	15.0	4.0
4.5	15.0	15.0	15.0	15.0	15.0	15.0	4.5
5.0	15.0	15.0	15.0	15.0	15.0	15.0	5.0
6.0	15.0	15.0	15.0	15.0	15.0	15.0	6.0
7.0	12.1	15.0	15.0	15.0	15.0	15.0	7.0
8.0		11.7	14.0	15.0	15.0	15.0	8.0
9.0				15.0	15.0	15.0	9.0
10.0				15.0	15.0	15.0	10.0
11.0				15.0	15.0	15.0	11.0
12.0				15.0	15.0	15.0	12.0
14.0					15.0	15.0	14.0
16.0					11.8	13.8	16.0
18.0						10.6	18.0
20.0						8.0	20.0
22.0						6.2	22.0
標準フック	350t	350t	350t	350t	350t	350t	

※は旋回位置が前方・後方 限定の性能を示しています。

