

■ 6段ESPブーム+フルオートラフィングジブ性能表

カウンタウエイト 94t、アウトリガ張出幅 9.0m、アシストジャッキ

6段ESPブーム60.1m+1.7m+フルオートラフィングジブ

単位:t

フルオートラフィングジブ長さ(m)	11.1	11.1	11.1	11.1	19.1	19.1	19.1	19.1	27.1	27.1	27.1	27.1	35.1	35.1	35.1	35.1	m
ジブオフセット(°)	0	15	30	40	0	15	30	40	0	15	30	40	0	15	30	40	°
16.0	39.6																16.0
18.0	37.5	32.8			24.9				14.6								18.0
20.0	35.3	31.0			24.8				14.6				8.3				20.0
22.0	33.3	29.3	24.3	21.4	23.2	15.2			13.8				8.3				22.0
24.0	31.4	27.8	23.4	20.8	21.7	14.5			12.7				8.3				24.0
26.0	29.6	26.3	22.6	20.2	20.5	13.8	10.7		11.8	7.5			8.1				26.0
28.0	27.6	24.9	21.9	19.7	19.3	13.2	10.3	9.1	11.0	7.1			7.6				28.0
30.0	23.7	23.6	21.2	19.2	18.2	12.7	10.0	8.9	10.3	6.8			7.1	4.5			30.0
32.0	20.4	21.9	20.5	18.8	17.2	12.2	9.7	8.6	9.6	6.5	5.0		6.6	4.3			32.0
34.0	17.5	18.9	19.9	18.4	16.3	11.7	9.4	8.5	9.0	6.2	4.8	4.1	6.2	4.1			34.0
36.0	14.9	16.2	17.2	17.7	15.4	11.3	9.2	8.3	8.5	5.9	4.6	4.0	5.8	3.9			36.0
38.0	12.7	13.9	14.8	15.2	14.6	10.9	8.9	8.2	8.0	5.7	4.5	3.9	5.4	3.7	2.7		38.0
40.0	10.7	11.8	12.6	13.0	13.0	10.5	8.7	8.0	7.6	5.4	4.3	3.8	5.1	3.5	2.6		40.0
42.0	8.8	9.9	10.7	11.0	11.2	10.1	8.5	7.9	7.2	5.2	4.2	3.7	4.8	3.3	2.5	2.1	42.0
44.0	7.1	8.1	8.9	9.2	9.6	9.8	8.3	7.8	6.8	5.0	4.1	3.6	4.5	3.2	2.4	2.1	44.0
46.0	5.5	6.5	7.2	7.4	8.0	9.5	8.2	7.6	6.5	4.8	3.9	3.5	4.3	3.0	2.3	2.0	46.0
48.0		5.0	5.6	5.8	6.5	8.1	8.0	7.5	6.2	4.7	3.8	3.5	4.0	2.9	2.2	1.9	48.0
50.0				4.3	5.2	6.7	7.8	7.4	5.9	4.5	3.7	3.4	3.8	2.8	2.2	1.9	50.0
55.0							4.5	4.8	4.6	4.1	3.5	3.2	3.3	2.5	2.0	1.7	55.0
60.0											3.3	3.1		2.2	1.8	1.6	60.0
65.0															1.7	1.5	65.0
70.0																	70.0
75.0																	75.0
80.0																	80.0
ブーム伸縮状態(伸縮割合)(%)	1	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	1
	2	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	2
	3	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	3
	4	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	4
	5	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	5
ID	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	ID
ブーム角度の範囲無負荷時(°)	52~82	52~82	53~82	51~82	54~82	57~82	54~82	54~82	54~82	58~82	56~82	57~82	58~82	59~82	59~82	60~82	°
標準巻掛本数	5	5	5	5	3	3	3	3	2	2	2	2	1	1	1	1	
標準フック	80t	80t	80t	80t	80t	80t	80t	80t	25t	25t	25t	25t	12.5t	12.5t	12.5t	12.5t	

カウンタウエイト 94t、アウトリガ張出幅 9.0m、アシストジャッキ

6段ESPブーム64.0m+1.7m+フルオートラフィングジブ

単位:t

フルオートラフィングジブ長さ(m)	11.1	11.1	11.1	11.1	19.1	19.1	19.1	19.1	27.1	27.1	27.1	27.1	35.1	35.1	35.1	35.1	m
ジブオフセット(°)	0	15	30	40	0	15	30	40	0	15	30	40	0	15	30	40	°
16.0	28.5																16.0
18.0	28.5				18.1												18.0
20.0	28.5	28.5			18.1				10.9								20.0
22.0	28.5	27.6	24.5		18.1				10.9				6.5				22.0
24.0	28.5	26.2	23.7	20.9	18.1	14.6			10.9				6.5				24.0
26.0	27.8	24.9	22.9	20.3	18.1	13.9			10.9	7.5			6.5				26.0
28.0	26.3	23.6	21.8	19.8	18.1	13.3	10.3		10.9	7.2			6.5				28.0
30.0	23.5	22.4	20.8	19.4	18.1	12.8	10.0	8.5	10.5	6.9			6.5				30.0
32.0	20.1	21.3	19.8	18.9	17.7	12.3	9.7	8.3	9.8	6.6	5.0		6.5	4.3			32.0
34.0	17.2	18.7	18.9	18.4	16.8	11.9	9.5	8.2	9.2	6.3	4.8		6.4	4.1			34.0
36.0	14.7	16.0	17.1	17.6	15.9	11.4	9.2	8.0	8.7	6.0	4.6	4.0	6.0	3.9			36.0
38.0	12.5	13.7	14.6	15.1	14.7	11.0	9.0	7.9	8.2	5.8	4.5	3.9	5.6	3.7	2.7		38.0
40.0	10.5	11.6	12.5	12.9	12.7	10.7	8.8	7.7	7.8	5.5	4.3	3.8	5.3	3.5	2.6		40.0
42.0	8.6	9.7	10.5	10.9	10.9	10.3	8.6	7.6	7.4	5.3	4.2	3.7	5.0	3.4	2.5		42.0
44.0	6.8	7.9	8.8	9.1	9.3	10.0	8.4	7.5	7.0	5.1	4.1	3.6	4.7	3.2	2.4	2.1	44.0
46.0		6.3	7.0	7.3	7.7	9.3	8.2	7.4	6.7	4.9	4.0	3.6	4.4	3.1	2.3	2.0	46.0
48.0			5.4	5.7	6.2	7.9	8.1	7.3	6.4	4.8	3.9	3.5	4.2	2.9	2.3	1.9	48.0
50.0						6.4	7.6	7.2	6.1	4.6	3.8	3.4	4.0	2.8	2.2	1.9	50.0
55.0										4.2	3.5	3.3	3.5	2.5	2.0	1.7	55.0
60.0													3.1	2.3	1.8	1.6	60.0
65.0															1.7	1.5	65.0
70.0																	70.0
75.0																	75.0
80.0																	80.0
ブーム伸縮状態(伸縮割合)(%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
	2	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
	3	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	3
	4	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	4
	5	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	5
ID	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	ID
ブーム角度の範囲無負荷時(°)	57~82	57~82	56~82	56~82	58~82	59~82	62~82	62~82	60~82	60~82	63~82	60~82	60~82	61~82	61~82	62~82	°
標準巻掛本数	5	5	5	5	3	3	3	3	2	2	2	2	1	1	1	1	
標準フック	80t	80t	80t	80t	80t	80t	80t	80t	25t	25t	25t	25t	12.5t	12.5t	12.5t	12.5t	