

スーパーラフィングジブ(SLジブ)

■定格総荷重表

■40.9mブーム+10.5m SLジブ

A性能

作業半径 (m)	0°		15°		30°		45°		60°	
	角度	荷重	角度	荷重	角度	荷重	角度	荷重	角度	荷重
9.0	81.0	22.0								
10.0	78.9	22.0								
11.0	77.8	22.0								
12.0	76.7	22.0	79.5	21.3						
14.0	74.5	22.0	77.1	19.7	79.5	15.8				
16.0	72.3	22.0	74.9	18.4	77.2	15.0	78.8	12.4		
18.0	70.0	21.7	72.6	17.2	74.8	14.4	76.5	12.0	77.3	9.8
20.0	67.7	19.4	70.3	15.9	72.5	13.8	74.1	11.7	74.8	9.6
22.0	65.4	17.4	67.9	14.6	70.1	12.8	71.5	11.5	72.1	9.6
24.0	63.0	15.6	65.5	13.4	67.6	11.9	68.9	11.0	69.3	9.5
26.0	60.5	14.0	63.0	12.4	65.0	11.2	66.1	10.4	66.3	9.5
28.0	58.0	12.7	60.5	11.5	62.4	10.5	63.2	9.9		
30.0	55.3	11.5	57.9	10.7	59.7	9.8	60.2	9.4		
32.0	52.6	10.5	55.1	9.9	56.8	9.2	57.2	8.9		
34.0	49.8	9.6	52.3	9.1	53.9	8.7	54.1	8.4		
36.0	46.9	8.7	49.3	8.4	50.7	8.1	51.0	8.0		
38.0	43.7	7.7	46.1	7.7	47.4	7.5				
40.0	40.4	6.5	42.6	7.0	43.7	7.0				
42.0	36.7	5.4	38.8	5.8	39.6	6.0				
44.0	32.6	4.3	34.5	4.7	35.0	4.8				
46.0	27.8	3.4	29.5	3.7						
48.0	21.9	2.5	23.1	2.6						
θ(°)	17~83		17~83		30~83		45~83		60~83	
標準フック	22 ton									
フック荷重	880 kg									
フック掛数	2本									

(単位: ton)

■40.9mブーム+18.9m SLジブ

A性能

作業半径 (m)	0°		15°		30°		45°		60°	
	角度	荷重	角度	荷重	角度	荷重	角度	荷重	角度	荷重
10.0	81.1	10.0								
11.0	80.1	10.0								
12.0	79.2	10.0								
14.0	77.3	10.0								
16.0	75.4	10.0	79.4	10.0						
18.0	73.4	10.0	77.4	10.0						
20.0	71.5	10.0	75.4	10.0	79.2	7.7				
22.0	69.5	10.0	73.4	9.4	77.2	7.4	80.3	6.0		
24.0	67.5	10.0	71.4	8.8	75.1	7.1	78.1	5.8	80.4	4.6
26.0	65.4	10.0	69.3	8.3	73.0	6.8	75.9	5.6	77.7	4.5
28.0	63.3	9.4	67.2	7.8	70.9	6.5	73.5	5.5	75.0	4.4
30.0	61.1	8.7	65.1	7.4	68.6	6.3	71.1	5.3	72.4	4.4
32.0	58.9	8.1	62.9	7.0	66.4	6.0	68.7	5.2	69.7	4.4
34.0	56.7	7.5	60.7	6.7	64.1	5.8	66.2	5.1	67.0	4.3
36.0	54.5	7.0	58.4	6.3	61.7	5.6	63.6	5.0	64.1	4.3
38.0	52.2	6.6	56.0	6.1	59.2	5.4	60.9	4.9		
40.0	49.9	6.2	53.6	5.8	56.6	5.2	57.9	4.8		
42.0	47.4	5.8	51.1	5.4	53.9	5.0	54.8	4.7		
44.0	44.8	5.5	48.4	5.1	50.9	4.8	51.5	4.6		
46.0	42.0	5.2	45.4	4.8	47.8	4.5				
48.0	38.9	4.8	42.4	4.5	44.3	4.3				
50.0	35.5	3.9	38.9	4.2	40.5	4.1				
52.0	31.6	3.1	35.0	3.6	36.0	3.9				
54.0	27.3	2.4	30.4	2.8						
56.0	22.2	1.7	24.5	2.0						
θ(°)	17~83		20~83		30~83		45~83		60~83	
標準フック	11.4 ton									
フック荷重	420 kg									
フック掛数	1本									

(単位: ton)

■40.9mブーム+27.3m SLジブ

A性能

作業半径 (m)	0°		15°		30°		45°		60°	
	角度	荷重	角度	荷重	角度	荷重	角度	荷重	角度	荷重
12.0	80.2	6.5								
14.0	78.6	6.5								
16.0	77.0	6.5								
18.0	75.4	6.5								
20.0	73.8	6.5	79.5	6.1						
22.0	72.1	6.5	77.8	5.7						
24.0	70.5	6.5	76.1	5.4						
26.0	68.8	6.5	74.4	5.1	79.2	4.1				
28.0	67.1	6.5	72.6	4.9	77.5	3.9				
30.0	65.3	6.1	70.8	4.7	75.6	3.8	79.3	3.1		
32.0	63.5	5.8	69.0	4.5	73.6	3.6	77.5	3.0		
34.0	61.6	5.4	67.1	4.3	71.6	3.5	75.5	2.9	77.9	2.5
36.0	59.7	5.1	65.1	4.1	69.5	3.3	73.4	2.8	75.4	2.4
38.0	57.8	4.8	63.2	3.9	67.3	3.2	71.2	2.7	72.9	2.4
40.0	55.9	4.4	61.2	3.8	65.1	3.1	68.8	2.7	70.3	2.3
42.0	53.8	4.1	59.1	3.6	62.8	3.0	66.3	2.6	67.6	2.3
44.0	51.8	3.9	57.0	3.5	60.6	2.9	63.7	2.6	64.7	2.3
46.0	49.7	3.6	54.9	3.3	58.2	2.8	60.9	2.5		
48.0	47.6	3.4	52.7	3.1	55.9	2.8	58.1	2.5		
50.0	45.3	3.2	50.4	3.0	53.4	2.7	55.3	2.5		
52.0	43.0	3.0	47.9	2.9	50.8	2.6	52.4	2.5		
54.0	40.5	2.8	45.3	2.7	48.0	2.5				
56.0	37.7	2.6	42.5	2.6	44.9	2.4				
58.0	34.7	2.5	39.3	2.5	41.3	2.4				
60.0	31.3	2.1	35.7	2.4	37.0	2.3				
62.0	27.4	1.6	31.5	2.0						
64.0			26.1	1.4						
θ(°)	20~83		20~83		30~83		45~83		60~83	
標準フック	11.4 ton									
フック荷重	880 kg									
フック掛数	1本									

(単位: ton)

■50mブーム+10.5m SLジブ

A性能

作業半径 (m)	0°		15°		30°		45°		60°	
	角度	荷重	角度	荷重	角度	荷重	角度	荷重	角度	荷重
11.0	80.6	17.0								
12.0	79.7	17.0								
14.0	77.9	17.0	80.2	17.0						
16.0	75.9	17.0	78.3	17.0	80.0	15.3				
18.0	74.0	17.0	76.4	17.0	78.0	14.7	79.6	12.3	80.1	9.8
20.0	72.1	16.4	74.4	15.2	76.2	13.4	77.5	12.0	78.1	9.7
22.0	70.2	14.4	72.4	13.5	74.2	12.3	75.4	11.3	76.0	9.6
24.0	68.2	12.6	70.4	12.0	72.2	11.2	73.2	10.4	73.9	9.5
26.0	66.2	11.2	68.3	10.7	70.1	10.3	71.1	9.7	71.7	9.3
28.0	64.1	9.9	66.2	9.5	68.0	9.2	68.9	9.0	69.3	8.7
30.0	62.0	8.9	64.0	8.5	65.8	8.3	66.6	8.2	67.0	8.1
32.0	59.8	7.9	61.9	7.7	63.5	7.5	64.3	7.4		
34.0	57.6	7.0	59.6	6.9	61.2	6.8	62.0	6.7		
36.0	55.3	6.3	57.4	6.2	58.8	6.1	59.5	6.1		
38.0	53.0	5.6	55.0	5.5	56.4	5.5	57.0	5.5		
40.0	50.6	4.9	52.6	5.0	53.8	4.9	54.3	4.9		
42.0	48.1	4.3	50.1	4.4	51.2	4.4	51.5	4.4		
44.0	45.5	3.7	47.5	3.9	48.4	4.0				
46.0	42.7	3.2	44.6	3.3	45.5	3.4				
48.0	39.8	2.3	41.5	2.7	42.3	2.9				
50.0					38.9	2.0				
θ(°)	26~83		26~83		30~83		45~83		60~83	
標準フック	22 ton									
フック荷重	880 kg									
フック掛数	2本									

(単位: ton)