

■定格総荷重表

■22.7mブーム+4.35m+30mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
14.0 (m)	30.0				
16.0	30.0				
18.0	30.0				
20.0	30.0	29.3			
22.0	29.6	27.3			
24.0	29.6	25.6	22.4		
26.0	26.5	24.0	21.2		
28.0	23.7	22.7	20.2	16.4	
30.0	21.1	21.5	19.3	15.8	
32.0	18.9	19.9	18.5	15.3	12.0
34.0	17.0	17.9	17.7	14.8	11.7
36.0	15.3	16.2	17.0	14.4	11.5
38.0	13.9	14.6	15.3	14.0	11.4
40.0	12.6	13.2	13.9	13.7	11.3
45.0	9.9	10.3	10.8	11.2	
50.0	7.6	8.0	8.2		
θ(°)	10~83	20~83	30~83	45~83	60~83
標準フック	65 ton				
フック重量	1000 kg				
巻掛本数	4本				

(単位: ton)

■31.8mブーム+4.35m+30mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
16.0 (m)	19.0				
18.0	18.6				
20.0	18.4				
22.0	18.2	18.2			
24.0	18.0	18.0			
26.0	17.8	17.6	15.8		
28.0	17.6	17.1	15.4		
30.0	17.5	16.6	15.1	12.7	
32.0	17.4	16.2	14.7	12.5	
34.0	16.4	15.8	14.4	12.3	10.1
36.0	14.9	15.5	14.2	12.1	10.1
38.0	13.4	14.3	14.0	12.0	10.0
40.0	12.1	12.9	13.7	11.9	10.0
45.0	9.3	10.0	10.6	11.3	10.0
50.0	7.0	7.6	8.2	8.6	
55.0	5.1	5.5	5.9		
60.0	3.4	3.7			
θ(°)	14~83	20~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■40.9mブーム+4.35m+30mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
18.0 (m)	11.5				
20.0	11.5				
22.0	11.5				
24.0	11.0	11.0			
26.0	11.0	11.0			
28.0	11.0	11.0	11.0		
30.0	11.0	11.0	11.0		
32.0	11.0	11.0	11.0	11.0	
34.0	11.0	11.0	11.0	11.0	
36.0	11.0	11.0	11.0	11.0	10.2
38.0	10.5	10.8	11.0	11.0	10.2
40.0	9.6	10.4	10.8	11.0	10.1
45.0	7.8	8.4	9.0	9.9	10.1
50.0	6.3	6.8	7.3	8.0	
55.0	4.5	5.1	5.6	6.2	
60.0	2.8	3.3	3.7		
65.0			1.9		
θ(°)	23~83	23~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+4.35m+30mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
20.0 (m)	6.6				
22.0	6.6				
24.0	6.6	6.6			
26.0	6.6	6.6			
28.0	6.6	6.6	6.6		
30.0	6.6	6.6	6.6		
32.0	6.6	6.6	6.6		
34.0	6.6	6.6	6.6	5.8	
36.0	6.6	6.6	6.6	5.8	
38.0	6.3	6.5	6.6	5.7	4.5
40.0	6.0	6.3	6.5	5.6	4.5
45.0	5.1	5.7	6.0	5.6	4.5
50.0	3.9	4.4	4.9	5.6	4.5
55.0	2.8	3.3	3.7	4.2	
60.0	1.9	2.3	2.7	3.1	
θ(°)	40~83	40~83	40~83	45~83	64~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■31.8mブーム+4.35m+40mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
20.0 (m)	11.0				
22.0	11.0				
24.0	11.0				
26.0	11.0	11.0			
28.0	11.0	11.0			
30.0	11.0	11.0			
32.0	11.0	11.0	10.7		
34.0	11.0	11.0	10.2		
36.0	11.0	11.0	9.7		
38.0	11.0	10.7	9.3	7.8	
40.0	11.0	10.2	8.9	7.5	
45.0	10.4	9.1	8.0	7.0	6.2
50.0	8.3	8.2	7.4	6.5	6.0
55.0	6.4	7.2	6.8	6.2	5.9
60.0	4.8	5.5	6.0	6.0	
65.0	3.4	3.9	4.3		
70.0	2.2	2.4			
θ(°)	15~83	20~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■40.9mブーム+4.35m+40mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
22.0 (m)	7.5				
24.0	7.5				
26.0	7.5				
28.0	7.5	7.5			
30.0	7.5	7.5			
32.0	7.5	7.5			
34.0	7.5	7.5	7.5		
36.0	7.5	7.5	7.5		
38.0	7.5	7.5	7.5		
40.0	7.5	7.5	7.5	7.5	
45.0	7.5	7.5	7.5	7.2	6.3
50.0	6.3	7.0	7.4	6.7	6.1
55.0	5.1	5.7	6.3	6.4	5.9
60.0	4.1	4.6	5.0	5.7	
65.0	2.7	3.3	3.9	4.5	
70.0		2.0	2.4		
θ(°)	25~83	25~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+4.35m+40mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
24.0 (m)	4.5				
26.0	4.5				
28.0	4.5				
30.0	4.5	4.5			
32.0	4.5	4.5			
34.0	4.5	4.5			
36.0	4.5	4.5	4.5		
38.0	4.5	4.5	4.5		
40.0	4.5	4.5	4.5		
45.0	4.5	4.5	4.5	3.7	
50.0	3.8	4.4	4.4	3.6	2.7
55.0	2.8	3.4	3.9	3.5	2.7
60.0	2.0	2.5	2.9	3.5	2.7
65.0		1.7	2.1	2.7	
70.0				1.7	
θ(°)	45~83	45~83	45~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■31.8mブーム+4.35m+47mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
22.0 (m)	7.5				
24.0	7.5				
26.0	7.5				
28.0	7.5				
30.0	7.5	7.3			
32.0	7.5	7.0			
34.0	7.5	6.7			
36.0	7.3	6.5	5.8		
38.0	7.0	6.2	5.6		
40.0	6.7	6.0	5.5		
45.0	6.1	5.5	5.0	4.5	
50.0	5.6	5.1	4.8	4.4	4.2
55.0	5.2	4.8	4.5	4.2	4.1
60.0	4.8	4.6	4.3	4.2	4.1
65.0	4.0	4.4	4.2	4.2	
70.0	2.7	3.3	3.7	4.1	
θ(°)	25~83	25~83	30~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■40.9mブーム+4.35m+47mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
24.0 (m)	5.5				
26.0	5.5				
28.0	5.5				
30.0	5.5				
32.0	5.5	5.5			
34.0	5.5	5.5			
36.0	5.5	5.5			
38.0	5.5	5.5	5.5		
40.0	5.5	5.5	5.5		
45.0	5.5	5.5	5.2		
50.0	5.5	5.4	4.9	4.4	
55.0	4.9	5.1	4.7	4.3	4.1
60.0	3.9	4.5	4.5	4.2	4.1
65.0	3.0	3.6	4.1	4.1	4.1
70.0	1.9	2.7	3.2	3.8	
75.0				2.4	
θ(°)	33~83	33~83	33~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+4.35m+47mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
26.0 (m)	3.3				
28.0	3.3				
30.0	3.3				
32.0	3.3				
34.0	3.3	3.3			
36.0	3.3	3.3			
38.0	3.3	3.3			
40.0	3.3	3.3	3.1		
45.0	3.3	3.3	3.1		
50.0	3.3	3.1	3.1	2.5	
55.0	2.5	2.8	2.8	2.4	1.6
60.0	1.7	2.3	2.7	2.4	1.6
65.0		1.5	2.1	2.4	1.6
70.0				2.0	1.6
θ(°)	48~83	48~83	48~83	49~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■40.9mブーム+4.35m+54mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'	60'
26.0 (m)	3.8				
28.0	3.8				
30.0	3.8				
32.0	3.8				
34.0	3.8	3.7			
36.0	3.8	3.5			
38.0	3.8	3.3			
40.0	3.8	3.2			
45.0	3.4	2.8	2.4		
50.0	3.0	2.5	2.2		
55.0	2.7	2.3	2.0	1.7	
60.0	2.4	2.1	1.9	1.6	1.5
65.0	2.2	1.9	1.7	1.5	1.5
70.0	2.0	1.8	1.6	1.5	1.5
75.0		1.7	1.6	1.5	
80.0			1.5	1.5	
θ(°)	40~83	40~83	40~83	45~83	60~83
標準フック	22 ton				
フック重量	880 kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+4.35m+54mヘビーリフトジブ A性能

作業半径	10'	20'	30'	45'
28.0 (m)	2.5			
30.0	2.5			
32.0	2.5			
34.0	2.5			
36.0	2.5	2.5		
38.0	2.5	2.5		
40.0	2.5	2.5		
45.0	2.5	2.5	2.4	
50.0	2.5	2.5	2.2	
55.0	2.2	2.2	2.0	1.5
60.0		2.1	1.9	
65.0			1.8	
θ(°)	51~83	52~83	52~83	55~83
標準フック	22 ton			
フック重量	880 kg			
巻掛本数	2本			

(単位: ton)