

■定格総荷重表

■44.1mブーム+45mヘビーリフトジブ (S性能)

作業半径	10°	20°	30°	45°	60°
24m	40.0				
26m	40.0				
28m	40.0				
30m	40.0				
32m	40.0	40.0			
34m	40.0	39.5			
36m	37.8	37.7			
38m	35.4	36.1	31.1		
40m	33.1	34.6	30.0		
42m	30.9	32.5	29.0		
44m	29.0	30.4	28.0		
46m	27.2	28.6	27.1	21.6	
48m	25.6	26.8	26.3	21.1	
50m	24.1	25.2	25.5	20.6	15.8
55m	20.7	21.8	22.8	19.6	15.3
60m	17.2	18.4	19.6	18.7	15.0
65m	14.3	15.3	16.3	17.4	
70m	11.9	12.7	13.4	14.2	
75m	9.8	10.4	10.9		
80m	8.0	8.4	8.7		
θ(°)	10°~83°	20°~83°	30°~83°	45°~83°	60°~83°
標準フック	70 t フック(1,900kg)				
巻掛本数	4				

(単位: ton)

■44.1mブーム+54mヘビーリフトジブ (S性能)

作業半径	10°	20°	30°	45°	60°
28m	32.0				
30m	32.0				
32m	32.0				
34m	32.0				
36m	32.0	29.9			
38m	32.0	29.1			
40m	31.4	28.4			
42m	30.4	27.7			
44m	28.7	27.0	23.5		
46m	27.1	26.1	22.7		
48m	25.6	25.0	21.9		
50m	24.1	24.1	21.2		
55m	20.7	21.9	19.6	15.6	
60m	17.8	19.0	18.2	14.7	11.1
65m	14.9	16.2	17.0	14.0	10.7
70m	12.4	13.5	14.6	13.4	10.5
75m	10.3	11.2	12.1	12.9	
80m	8.4	9.2	9.9	10.6	
85m	6.7	7.4	7.9		
90m	5.1	5.6			
θ(°)	10°~83°	20°~83°	30°~83°	45°~83°	60°~83°
標準フック	70 t フック(1,900kg)				
巻掛本数	4				

(単位: ton)

■定格総荷重表

■44.1mブーム+63mヘビーリフトジブ (S性能)

作業半径	10°	20°	30°	45°	60°
30m	22.0				
32m	22.0				
34m	22.0				
36m	22.0				
38m	21.6				
40m	20.9				
42m	20.2	18.0			
44m	19.6	17.5			
46m	19.0	17.1			
48m	18.4	16.6			
50m	17.9	16.2	14.8		
55m	16.7	15.2	14.0		
60m	15.6	14.4	13.3	12.2	
65m	14.7	13.6	12.7	11.8	
70m	13.2	13.0	12.3	11.4	8.2
75m	11.0	12.2	11.9	10.8	7.9
80m	9.1	10.1	11.1	10.3	7.8
85m	7.4	8.3	9.1	9.9	
90m	5.7	6.6	7.3	8.0	
95m	4.2	4.9	5.4		
100m		3.3			
θ(°)	23°~83°	23°~83°	30°~83°	45°~83°	60°~83°
標準フック	24 t フック(1,070kg)				
巻掛本数	2				

(単位: ton)

■44.1mブーム+72mヘビーリフトジブ (S性能)

作業半径	10°	20°	30°	45°	60°
32m	15.0				
34m	14.6				
36m	13.9				
38m	13.4				
40m	12.8				
42m	12.3				
44m	11.8				
46m	11.4	9.9			
48m	10.9	9.5			
50m	10.5	9.2			
55m	9.6	8.5	7.5		
60m	8.8	7.8	7.0		
65m	8.1	7.3	6.5		
70m	7.5	6.8	6.2	5.5	
75m	6.9	6.3	5.8	5.3	
80m	6.5	6.0	5.5	5.1	5.0
85m	6.1	5.6	5.3	5.0	5.0
90m	5.7	5.4	5.2	5.0	4.9
95m	4.7	5.2	5.1	5.0	
100m	3.4	4.2	4.9	5.0	
θ(°)	25°~83°	32°~83°	34°~83°	45°~83°	60°~83°
標準フック	24 t フック(1,070kg)				
巻掛本数	2				

(単位: ton)