

■定格総荷重表

1.アウトリガ最大(4.4m)張出[全周]

()内はRK70型の値です。単位: Ton

ブーム長さ 作業半径	主ブーム					ジブ	
	4.9m	8.1m	11.3m	14.5m	17.7m	16.4m	21.2m
1.0m	4.90(7.00)	4.90					
1.5m	4.90(7.00)	4.90	4.90	4.00			
2.0m	4.90(7.00)	4.90	4.90	4.00		1.40	
2.5m	4.90(7.00)	4.90	4.90	4.00	4.00	1.40	
3.0m	4.90(6.10)	4.90	4.90	4.00	4.00	1.40	1.40
3.5m	4.90(5.30)	4.90	4.90	4.00	4.00	1.40	1.40
4.0m		4.50	4.50	4.00	4.00	1.40	1.40
4.5m		3.85	3.87	3.50	3.50	1.40	1.40
5.0m		3.33	3.37	3.11	3.13	1.40	1.40
5.5m		2.95	2.97	2.77	2.82	1.40	1.40
6.0m		2.62	2.65	2.50	2.56	1.40	1.40
7.0m		2.26(6.7m)	2.14	2.07	2.15	1.40	1.40
8.0m			1.77	1.75	1.84	1.40	1.40
9.0m			1.48	1.50	1.60	1.40	1.23
10.0m			1.25(9.9m)	1.30	1.40	1.40	1.09
11.0m				1.14	1.25	1.20	0.98
12.0m				0.96	1.07	1.02	0.89
13.0m				0.78	0.88	0.85	0.82
14.0m				0.77(13.1m)	0.73	0.70	0.75
15.0m					0.60	0.59	0.69
16.0m					0.49		0.64
17.0m					0.46(16.3m)		0.57
18.0m							0.50
19.0m							0.41
20.0m							0.35(19.9m)
危険角度	—	—	—	—	—	—	—

2.アウトリガ中間(3.0m)張出[側方]

ブーム長さ 作業半径	主ブーム					ジブ	
	4.9m	8.1m	11.3m	14.5m	17.7m	16.4m	21.2m
1.0m	4.90(7.00)	4.90					
1.5m	4.90(7.00)	4.90	4.90	4.00			
2.0m	4.90(7.00)	4.90	4.90	4.00		1.40	
2.5m	4.90(7.00)	4.90	4.90	4.00	4.00	1.40	
3.0m	4.90(6.10)	4.90	4.90	4.00	4.00	1.40	1.40
3.5m	4.90(5.30)	4.90	4.90	4.00	4.00	1.40	1.40
4.0m		3.78	3.80	4.00	4.00	1.40	1.40
4.5m		3.07	3.00	3.30	3.15	1.40	1.40
5.0m		2.48	2.50	2.75	2.64	1.40	1.40
5.5m		2.05	2.10	2.28	2.24	1.40	1.40
6.0m		1.73	1.75	1.97	1.97	1.40	1.40
7.0m		1.46(6.7m)	1.20	1.42	1.50	1.40	1.40
8.0m			0.85	1.10	1.14	1.14	1.34
9.0m			0.60	0.83	0.91	0.91	1.06
10.0m			0.45(9.9m)	0.61	0.71	0.70	0.87
11.0m				0.43	0.54	0.54	0.71
12.0m				0.29	0.39	0.39	0.58
13.0m				0.18	0.27	0.27	0.46
14.0m				0.17(13.1m)	0.18	0.17	0.36
15.0m							0.27
16.0m							0.20
17.0m							0.13
18.0m							
危険角度	—	—	—	—	30°	21°	30°