

■定格総荷重表

[ジブ](23.8mブーム)

| アウトリガ最大張出(4.7m) | | | | | | | | | | | | | | -全周- | | | | | | | | | | |
|-----------------|-----------------|----------|---------|----------|---------|----------|---------|----------|-----------------|----------|---------|----------|---------|----------|---------|----------|-------|--|--|--|-------|--|--|--|
| ジブ長さ | 23.8mブーム+3.6mジブ | | | | | | | | 23.8mブーム+5.5mジブ | | | | | | | | | | | | | | | |
| オフセット | 5° | | 25° | | 45° | | 60° | | 5° | | 25° | | 45° | | 60° | | | | | | | | | |
| ブーム角度 | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | | | | | | | | |
| 82° | 4.1 | 1.6 | 5.4 | 1.4 | 6.3 | 1.0 | 6.6 | 0.65 | 4.5 | 1.0 | 6.5 | 1.0 | 7.8 | 0.65 | 8.4 | 0.4 | | | | | | | | |
| 80° | 5.1 | 1.6 | 6.4 | 1.4 | 7.2 | 1.0 | 7.5 | 0.65 | 5.6 | 1.0 | 7.6 | 1.0 | 8.8 | 0.65 | 9.3 | 0.4 | | | | | | | | |
| 75° | 7.6 | 1.55 | 8.7 | 1.2 | 9.4 | 0.93 | 9.6 | 0.65 | 8.3 | 1.0 | 10.1 | 0.85 | 11.1 | 0.63 | 11.5 | 0.4 | | | | | | | | |
| 70° | 9.9 | 1.25 | 11.0 | 1.0 | 11.6 | 0.85 | 11.7 | 0.65 | 10.8 | 1.0 | 12.4 | 0.72 | 13.3 | 0.58 | 13.5 | 0.4 | | | | | | | | |
| 65° | 12.1 | 1.05 | 13.1 | 0.9 | 13.6 | 0.77 | 13.6 | 0.65 | 13.1 | 0.81 | 14.6 | 0.61 | 15.4 | 0.52 | 15.5 | 0.4 | | | | | | | | |
| 60° | 14.2 | 0.9 | 15.1 | 0.8 | 15.5 | 0.7 | 15.5 | 0.65 | 15.3 | 0.69 | 16.7 | 0.55 | 17.3 | 0.48 | 17.3 | 0.4 | | | | | | | | |
| 55° | 16.1 | 0.72 | 16.9 | 0.66 | 17.3 | 0.65 | | | 17.4 | 0.58 | 18.6 | 0.5 | 19.1 | 0.45 | | | | | | | | | | |
| 50° | 17.9 | 0.55 | 18.6 | 0.53 | 18.9 | 0.52 | | | 19.3 | 0.49 | 20.4 | 0.44 | 20.7 | 0.4 | | | | | | | | | | |
| 45° | 19.5 | 0.4 | 20.1 | 0.37 | 20.3 | 0.4 | | | 21.0 | 0.36 | 21.9 | 0.34 | 22.1 | 0.35 | | | | | | | | | | |
| 40° | 21.0 | 0.28 | 21.5 | 0.27 | | | | | 22.5 | 0.23 | 23.3 | 0.24 | | | | | | | | | | | | |
| 35° | 22.3 | 0.2 | 22.7 | 0.19 | | | | | | | | | | | | | | | | | | | | |
| A(°) | 34~82 | | | | 44~82 | | | | 59~82 | | | | 39~82 | | | | 44~82 | | | | 59~82 | | | |

A:ブーム角度の範囲(無負荷時)

[ジブ](23.8mブーム)

| アウトリガ中間張出(4.3m) | | | | | | | | | | | | | | -側方- | | | | | | |
|-----------------|-----------------|----------|---------|----------|---------|----------|---------|----------|-----------------|----------|---------|----------|---------|----------|---------|----------|-------|--|--|--|
| ジブ長さ | 23.8mブーム+3.6mジブ | | | | | | | | 23.8mブーム+5.5mジブ | | | | | | | | | | | |
| オフセット | 5° | | 25° | | 45° | | 60° | | 5° | | 25° | | 45° | | 60° | | | | | |
| ブーム角度 | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | | | | |
| 82° | 4.1 | 1.6 | 5.4 | 1.4 | 6.3 | 1.0 | 6.6 | 0.65 | 4.5 | 1.0 | 6.5 | 1.0 | 7.8 | 0.65 | 8.4 | 0.4 | | | | |
| 80° | 5.1 | 1.6 | 6.4 | 1.4 | 7.2 | 1.0 | 7.5 | 0.65 | 5.6 | 1.0 | 7.6 | 1.0 | 8.8 | 0.65 | 9.3 | 0.4 | | | | |
| 75° | 7.6 | 1.55 | 8.7 | 1.2 | 9.4 | 0.93 | 9.6 | 0.65 | 8.3 | 1.0 | 10.1 | 0.85 | 11.1 | 0.63 | 11.5 | 0.4 | | | | |
| 70° | 9.9 | 1.25 | 11.0 | 1.0 | 11.6 | 0.85 | 11.7 | 0.65 | 10.8 | 1.0 | 12.4 | 0.72 | 13.3 | 0.58 | 13.5 | 0.4 | | | | |
| 65° | 12.1 | 1.05 | 13.1 | 0.9 | 13.6 | 0.77 | 13.6 | 0.65 | 13.1 | 0.81 | 14.6 | 0.61 | 15.4 | 0.52 | 15.5 | 0.4 | | | | |
| 60° | 14.2 | 0.85 | 15.1 | 0.8 | 15.5 | 0.7 | 15.5 | 0.65 | 15.3 | 0.69 | 16.7 | 0.55 | 17.3 | 0.48 | 17.3 | 0.4 | | | | |
| 55° | 16.1 | 0.63 | 16.9 | 0.6 | 17.3 | 0.6 | | | 17.4 | 0.55 | 18.6 | 0.5 | 19.1 | 0.45 | | | | | | |
| 50° | 17.8 | 0.46 | 18.6 | 0.43 | 18.8 | 0.43 | | | 19.2 | 0.4 | 20.3 | 0.38 | 20.6 | 0.36 | | | | | | |
| 45° | 19.5 | 0.32 | 20.1 | 0.3 | 20.2 | 0.3 | | | 21.0 | 0.28 | 21.9 | 0.26 | 22.1 | 0.25 | | | | | | |
| 40° | 20.9 | 0.2 | 21.4 | 0.19 | | | | | | | | | | | | | | | | |
| A(°) | 39~82 | | | | 44~82 | | | | 59~82 | | | | 44~82 | | | | 59~82 | | | |

A:ブーム角度の範囲(無負荷時)

[ジブ](23.8mブーム)

| アウトリガ中間張出(3.5m) | | | | | | | | | | | | | | -側方- | | |
|-----------------|-----------------|----------|---------|----------|---------|----------|---------|----------|-----------------|----------|---------|----------|---------|----------|---------|----------|
| ジブ長さ | 23.8mブーム+3.6mジブ | | | | | | | | 23.8mブーム+5.5mジブ | | | | | | | |
| オフセット | 5° | | 25° | | 45° | | 60° | | 5° | | 25° | | 45° | | 60° | |
| ブーム角度 | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) |
| 82° | 4.1 | 1.6 | 5.4 | 1.4 | 6.3 | 1.0 | 6.6 | 0.65 | 4.5 | 1.0 | 6.5 | 1.0 | 7.8 | 0.65 | 8.4 | 0.4 |
| 80° | 5.1 | 1.6 | 6.4 | 1.4 | 7.2 | 1.0 | 7.5 | 0.65 | 5.6 | 1.0 | 7.6 | 1.0 | 8.8 | 0.65 | 9.3 | 0.4 |
| 75° | 7.6 | 1.55 | 8.7 | 1.2 | 9.4 | 0.93 | 9.6 | 0.65 | 8.3 | 1.0 | 10.1 | 0.85 | 11.1 | 0.63 | 11.5 | 0.4 |
| 70° | 9.9 | 1.25 | 11.0 | 1.0 | 11.6 | 0.85 | 11.7 | 0.65 | 10.8 | 1.0 | 12.4 | 0.72 | 13.3 | 0.58 | 13.5 | 0.4 |
| 65° | 12.0 | 0.83 | 13.0 | 0.75 | 13.6 | 0.74 | 13.6 | 0.65 | 13.1 | 0.75 | 14.6 | 0.61 | 15.4 | 0.52 | 15.5 | 0.4 |
| 60° | 14.0 | 0.56 | 15.0 | 0.52 | 15.5 | 0.5 | 15.4 | 0.49 | 15.1 | 0.49 | 16.6 | 0.42 | 17.3 | 0.4 | 17.3 | 0.38 |
| 55° | 15.9 | 0.34 | 16.8 | 0.31 | 17.1 | 0.3 | | | 17.1 | 0.3 | 18.4 | 0.27 | 19.0 | 0.24 | | |
| A(°) | 54~82 | | | | 59~82 | | | | 54~82 | | | | 59~82 | | | |

A:ブーム角度の範囲(無負荷時)

[ジブ](23.8mブーム)

| アウトリガ中間張出(2.5m) | | | | | | | | | | | | | | -側方- | | |
|-----------------|-----------------|----------|---------|----------|---------|----------|---------|----------|-----------------|----------|---------|----------|---------|----------|---------|----------|
| ジブ長さ | 23.8mブーム+3.6mジブ | | | | | | | | 23.8mブーム+5.5mジブ | | | | | | | |
| オフセット | 5° | | 25° | | 45° | | 60° | | 5° | | 25° | | 45° | | 60° | |
| ブーム角度 | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) |
| 82° | 4.1 | 1.6 | 5.4 | 1.4 | 6.3 | 1.0 | 6.6 | 0.65 | 4.5 | 1.0 | 6.5 | 1.0 | 7.8 | 0.65 | 8.4 | 0.4 |
| 75° | 7.5 | 1.15 | 8.6 | 0.95 | 9.4 | 0.8 | 9.6 | 0.65 | 8.3 | 1.0 | 10.0 | 0.8 | 11.1 | 0.63 | 11.5 | 0.4 |
| 70° | 9.7 | 0.61 | 10.8 | 0.53 | 11.5 | 0.48 | 11.6 | 0.48 | 10.5 | 0.52 | 12.2 | 0.44 | 13.2 | 0.38 | 13.5 | 0.37 |
| 65° | 11.8 | 0.28 | 12.8 | 0.24 | 13.4 | 0.22 | 13.4 | 0.22 | 12.7 | 0.22 | | | | | | |
| A(°) | 64~82 | | | | 64~82 | | | | 64~82 | | | | 69~82 | | | |

A:ブーム角度の範囲(無負荷時)

[ジブ](20.1mブーム)

| アウトリガ最大張出(4.7m) | | | | | | | | | | | | | | -全周- | | | | | | | | | | |
|-----------------|-----------------|----------|---------|----------|---------|----------|---------|----------|-----------------|----------|---------|----------|---------|----------|---------|----------|-------|--|--|--|-------|--|--|--|
| ジブ長さ | 20.1mブーム+3.6mジブ | | | | | | | | 20.1mブーム+5.5mジブ | | | | | | | | | | | | | | | |
| オフセット | 5° | | 25° | | 45° | | 60° | | 5° | | 25° | | 45° | | 60° | | | | | | | | | |
| ブーム角度 | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | 作業半径(m) | 定格総荷重(t) | | | | | | | | |
| 82° | 3.5 | 1.6 | 4.7 | 1.4 | 5.6 | 1.0 | 6.0 | 0.65 | 3.9 | 1.0 | 5.8 | 1.0 | 7.1 | 0.65 | 7.8 | 0.4 | | | | | | | | |
| 80° | 4.3 | 1.6 | 5.5 | 1.4 | 6.4 | 1.0 | 6.7 | 0.65 | 4.8 | 1.0 | 6.7 | 1.0 | 8.0 | 0.65 | 8.6 | 0.4 | | | | | | | | |
| 75° | 6.4 | 1.6 | 7.5 | 1.3 | 8.3 | 0.95 | 8.5 | 0.65 | 7.1 | 1.0 | 8.8 | 0.88 | 9.9 | 0.63 | 10.4 | 0.4 | | | | | | | | |
| 70° | 8.4 | 1.45 | 9.4 | 1.15 | 10.1 | 0.9 | 10.2 | 0.65 | 9.2 | 1.0 | 10.8 | 0.79 | 11.8 | 0.58 | 12.1 | 0.4 | | | | | | | | |
| 65° | 10.3 | 1.25 | 11.2 | 1.05 | 11.8 | 0.86 | 11.8 | 0.65 | 11.3 | 0.96 | 12.8 | 0.72 | 13.6 | 0.55 | 13.7 | 0.4 | | | | | | | | |
| 60° | 12.1 | 1.1 | 12.9 | 0.95 | 13.4 | 0.8 | 13.4 | 0.65 | 13.2 | 0.84 | 14.5 | 0.67 | 15.2 | 0.52 | 15.3 | 0.4 | | | | | | | | |
| 55° | 13.7 | 0.92 | 14.5 | 0.81 | 14.9 | 0.75 | | | 15.0 | 0.73 | 16.2 | 0.62 | 16.8 | 0.49 | | | | | | | | | | |
| 50° | 15.3 | 0.74 | 16.0 | 0.68 | 16.2 | 0.62 | | | 16.7 | 0.64 | 17.8 | 0.56 | 18.1 | 0.45 | | | | | | | | | | |
| 45° | 16.7 | 0.56 | 17.3 | 0.52 | 17.5 | 0.5 | | | 18.2 | 0.48 | 19.2 | 0.44 | 19.4 | 0.4 | | | | | | | | | | |
| 40° | 18.0 | 0.42 | 18.5 | 0.39 | | | | | 19.6 | 0.35 | 20.3 | 0.32 | | | | | | | | | | | | |
| 35° | 19.1 | 0.31 | 19.5 | 0.29 | | | | | 20.8 | 0.26 | 21.4 | 0.24 | | | | | | | | | | | | |
| 30° | 20.1 | 0.23 | 20.4 | 0.22 | | | | | | | | | | | | | | | | | | | | |
| A(°) | 29~82 | | | | 44~82 | | | | 59~82 | | | | 34~82 | | | | 44~82 | | | | 59~82 | | | |

A:ブーム角度の範囲(無負荷時)